



Low-E Tab In-Cavity Insulation



In-Cavity Insulation For Walls, Rafters, Crawlspace & More!



Cut To Length
And.....



.....Staple To Inside
Corner Of Joist

Save Energy. Save \$\$\$. Do More. With Less. Period.

For more information please visit our website at www.low-e.com
or call 1-800-BUY-LOWE (800-289-5693)

LOW-E TAB FEATURES & SPECIFICATIONS



- * Unique Pre-Crushed Tab Design For Easy Install
- * Increases Energy Savings
- * For Use In Walls, Rafters, Crawlspace, Etc.
- * Can Be Used With Mass Insulation
- * Reflects Up To 97% Of Radiant Heat
- * Superior Thermal Performance
- * Improves Insulation System Performance
- * Insect, Bird, Mold & Mildew Resistant
- * Excellent Vapor Barrier
- * Installs Easily With A Razor Knife

PRODUCT CODES: 16LFLC, 18LFLC*, 24LFLC

PRODUCT DIMENSIONS & DESCRIPTION: Double sided scrimmed aluminum foil laminated to polyethylene foam (1/4" nominal thickness)

WIDTH: 16", 18", 24"

LENGTH: 125', 100', 125'

R-VALUE**: R-11 Down R-7.55 Up R-7.75 Horizontal

PERM RATING: ASTM E96 .008

EMITTANCE: ASTM C1371 0.03

FULL SCALE FIRE TEST: NFPA-286 Passed

FLAME & SMOKE: ASTM E84 Flame Spread <25 Smoke Developed <50

*Available by special order

**R-Value results are obtained from ASTM C236



**Discover even more ways to lower
energy costs with ESP Low-E®
Insulation**

