



A Patented,
ICC Approved, Stand Alone,
Insulated Roofing Underlayment



Isn't It Time Your Roofing Underlayment Did More?



Thermal imaging of an attic without
 ThermaSheet® roofing underlayment.
 Temperature is 129°



Thermal imaging of the same attic WITH
 ThermaSheet® roofing underlayment.
 Temperature is 98°

Save Energy. Save \$\$\$. Do More. With Less. Period.

For more information please visit our website at www.low-e.com
 or call 1-800-BUY-LOWE (800-289-5693)



ICC EVALUATION
 SERVICE

ICC-ES Evaluation Report
 ESR-3652

Most Widely Accepted and Trusted

U.S. Patent No's.

ICC,CBC,CRC,FRC Evaluated Alternative Stand Alone Underlayment

10,570,612 & 11,492,798

LOW-E THERMASHEET® FEATURES & SPECIFICATIONS



UNDER SHINGLES



UNDER CLAY TILE



UNDER METAL



UNDER STONE COATED STEEL

- * Self Seals Around Fasteners
- * Lowers Attic Temperature
- * Increases Energy Savings
- * Great For New Or Re-Roofing
- * TDI, CA & FL Approved
- * Excellent Vapor Barrier
- * Built In Overlap Means Full Five Square Coverage
- * For Use Under Shingles, Metal Roof, Clay Tile & More

PRODUCT CODES: 4LMPX (1/8" nominal thickness), 4LFPX (7/32" nominal thickness)
WIDTH: 4'

LENGTH: 125' (with a 4" overlapping flange)

R-VALUE: Under shingles - 4LMPX 0.5, 4LFPX 1.03

R-VALUE*: R-6.4 downward heat flow only (with 1.5" airspace)

PERM RATING: ASTM E96 0.008

EMITTANCE: ASTM C1371 0.03

*System R-Value for this installation method was calculated using data from the Ashrae Handbook of Fundamentals.



Discover even more ways to lower energy costs with ESP Low-E® Insulation

