



Low-E Attic Floor Insulation



Save Energy. Save \$\$\$\$. Do More. With Less. Period.

For more information please visit our website at www.low-e.com
or call 1-800-BUY-LOWE (800-289-5693)

LOW-E ATTIC FLOOR INSULATION

FEATURES & SPECIFICATIONS

- * Saves Time and Money
- * Non-toxic, no fiberglass – no itching
- * Perforated, will not trap moisture
- * Installs easily with a razor knife
- * Superior thermal performance
- * Improves insulation system performance
- * Insect/Bird resistant
- * Can be used with mass insulations
- * Reflects up to 97% of radiant heat

PRODUCT CODES: 4PMPA-SL, 24PMPA-SL

PRODUCT DESCRIPTION: Double sided scrimless aluminum foil laminated to polyethylene foam, perforated (1/8" nominal thickness)

WIDTH: 4'

LENGTH: 125'

R-VALUE*: R-5.5 Down, R-2.3 Up

PERM RATING: ASTM E96 5.18 perms or 51.55 grams/(day-m²)

CRITICAL RADIANT FLUX: ASTM E970 >.12 w/cm² (no ignition)

EMITTANCE: ASTM C1371 0.03

* R-Value determined when placed over attic floor joist or existing insulation in joist area. R-Value includes core material value and low emittance air film value for upward and downward heat flow respectively. To get the marked R-Value, it is essential that this insulation be installed properly. If you do it yourself, get instructions and follow them carefully. To obtain installation instructions please call 1-800-289-5693.



Discover Even More Ways To Lower Energy Costs With ESP Low-E® Insulation

